

Rubber Roof Coating



Product description:



Rubber roof Coating is a unique high build coating designed specifically for the treatment of very damaged or leaky roofs.

It dries to be a thick rubbery coat, and can be applied in a very thick layer onto materials such as: Fibercement, concrete, tiles, plaster, roofing felts, steel, wood etc.

Furthermore it contains agents against growth of fungi, algae and lichens together with UV-absorbants.

The elasticity of this product even at -20°C is up to 700%.

Use and application:



Rubber Roof Coating must be applied to a clean and dry surface. It is important to apply plenty of paint especially on very poor or leaky surfaces. Very poor surfaces might benefit from establishing a net down into the paint and afterwards paint 1-2 times again. Remember the first layer must be dry before applying the second. In closed attics with bad or no ventilation it is recommended to ensure ventilation for every 30-40 m².

The best result for applying Rubber Roof Coating is by spraying.

Recommendation: Always make a test coat to ensure the compatibility of product and surface.

Technical data



Composition: Special Polymer, UV stable pigments and agents for preservation. **Colours:** Black, Antracite grey, pale grey, marron, mocha, tile red, aluminum. **Density:** Approx. 1,3 g/ml **Dry content:** Appr. 65w/w% and 50 w/v%

Gloss: 5-10 **Spreading rate:** Appr. 3 m²/l (depending on thickness) **Dilution:** Max. 20 % water **Drying time:** 1-2 hours by 20°C and 60% RH. (depending on thickness) **Repaintable:** 12-24 hours (depending on thickness)

Application conditions: The temperature must be 5°C - 30 °C and max. 80% RH. **Application method:** brush, roller or airless spray.

Cleaning: Water **VOC:** max. 40 g/l (Cat. A/c)

Storage: Cool, but free of frost in closed containers and out the reach of children.

Benefits

Thick film coating

It has the ability to be put on in a very thick layer

Very elastic and can be stretched for 500-700 %

Keeps its elasticity down to minus 20 °C

For leaky and damaged roofs

Iso Paint Nordic A/S
Tvaervej 8
6640 Lunderskov
Denmark

Phone +45 7633 3114
Fax +45 7633 3115

mail@isopaint.com
www.isopaint.com



ISO PAINT NORDIC A/S